



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S21743 - 5.5 Watt MR16 LED; GU10 base; 3000K; 120 Volt; 40 deg.
Beam Angle; 2-Card



ELECTRICAL

Technology:	LED
Watts:	5.5W
Volts:	120V
Lumens:	500L
CRI:	80+
Rg Value :	10
CCT (Kelvins):	3000K - Soft White
Beam Spread :	40
Hours Rated:	25000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable
Incandescent Equivalent :	50W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Power Factor :	0.7
Light Source:	LED
CBCP :	750
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923217432
Each Quantity:	1
Each Dimensions:	2.17 x 3.15 x 7.08

PHYSICAL

Base:	Bi Pin GU10
Shape:	MR16
Finish:	White
Lens Finish:	Clear
Dimensions (In.):	MOL: 2.2 - MOD: 1.97
Weight (Lbs.):	0.05
Material:	Plastic
Housing Color:	White
Lensed:	Lensed Lamp

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	NTEC21ENM000316
NOM Expiration Date:	1/24/2023
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S21743 - 5.5 Watt MR16 LED; GU10 base; 3000K; 120 Volt; 40 deg.
Beam Angle; 2-Card

DIMMER COMPATIBILITY

Lutron	AYCL-153P
Eaton	DALo6P-C2
Leviton	DSL06-1LZ
Leviton	DSM10
Eaton	DULO6P-C2
Leviton	DW6HD
Lutron	LECL-153PH
Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PD-10WX
Lutron	PD-6WCL
Lutron	RCL-153PNL
Eaton	RF9640-ND
Legrand	RH703PTUTC
Legrand	RHCL450PTC
Satco	S11268
Leviton	TSM10
Eaton	VSULO6D