



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S21804 - 9.8 Watt; A19 LED; 2700K; Candelabra base; 220 deg.
Beam Angle; 120 Volt



ELECTRICAL

Technology:	LED
Watts:	9.8W
Volts:	120V
Lumens:	800L
CRI:	80+
Rg Value :	7
CCT (Kelvins):	2700K - Warm White
Beam Spread :	220
Hours Rated:	25000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase
Incandescent Equivalent :	60W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Power Factor :	0.98
Light Source:	LED
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923218040
Each Quantity:	1
Each Dimensions:	2.44 x 2.44 x 4.80

PHYSICAL

Base:	Candelabra
Shape:	A19
Finish:	Frost
Dimensions (In.):	MOL: 4.331 - MOD: 2.362
Weight (Lbs.):	0.05
Material:	Plastic
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	LOG2059ENC003007
NOM Expiration Date:	6/9/2022
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	Not For Sale In: CA



S21804 - 9.8 Watt; A19 LED; 2700K; Candelabra base; 220 deg.
Beam Angle; 120 Volt

DIMMER COMPATIBILITY

Leviton	6672
Leviton	66ELV
Lutron	CTRP-253P
Lutron	DVRP-253P
Lutron	NTRP-250