



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S21859** - 3 Watt T6.5 LED Filament; Clear; Intermediate Base; 200 Lumens; 2700K



### ELECTRICAL

|                           |                                                             |
|---------------------------|-------------------------------------------------------------|
| Technology:               | LED                                                         |
| Watts:                    | 3W                                                          |
| Volts:                    | 120V                                                        |
| Lumens:                   | 200L                                                        |
| CRI:                      | 90+                                                         |
| Rg Value :                | 54                                                          |
| CCT (Kelvins):            | 2700K - Warm White                                          |
| Beam Spread :             | 300                                                         |
| Hours Rated:              | 15000                                                       |
| Dimmable:                 | Yes-Dimmable - 120V only                                    |
| Dimmable Down To %:       | 100 to 20 percent                                           |
| Dimming Type :            | Forward Phase or Reverse Phase or Phase Selectable or Triac |
| Incandescent Equivalent : | 25W                                                         |
| Operating Temperature :   | -20C (-4F) to +45C (+113F)                                  |
| Power Factor :            | 0.76                                                        |
| Light Source:             | LED Filament                                                |
| Voltage Type:             | AC Only                                                     |
| Warranty:                 | 2-Years                                                     |

### PACKAGING

|                  |                    |
|------------------|--------------------|
| Each UPC:        | 045923218590       |
| Each Quantity:   | 1                  |
| Each Dimensions: | 1.34 x 4.33 x 6.30 |

### INFO

|                    |                                      |
|--------------------|--------------------------------------|
| Installation Note: | Not for use in vapor tight fixtures. |
|--------------------|--------------------------------------|

### PHYSICAL

|                   |                      |
|-------------------|----------------------|
| Base:             | Intermediate         |
| Shape:            | T6.5                 |
| Finish:           | Clear                |
| Dimensions (In.): | MOL: 2.2 - MOD: 0.86 |
| Weight (Lbs.):    | 0.02                 |
| Material:         | Glass / Copper       |
| Housing Color:    | None                 |

### COMPLIANCE

|                             |                     |
|-----------------------------|---------------------|
| Safety Listing:             | cETLus - Listed     |
| Location Rating:            | Wet                 |
| Indoor/Outdoor:             | Indoor; Outdoor     |
| DLC Approved:               | No                  |
| BAA Compliant:              | No                  |
| Enclosure Rating:           | Enclosed Rated Lamp |
| Rated For Enclosed Fixture: | Yes                 |
| FCC Compliant:              | Yes                 |
| RoHS Compliant:             | Yes                 |
| Restrictions:               | No Restrictions     |



**S21859** - 3 Watt T6.5 LED Filament; Clear; Intermediate Base; 200 Lumens; 2700K

#### DIMMER COMPATIBILITY

|         |             |
|---------|-------------|
| Leviton | 6672        |
| Leviton | 6674        |
| Satco   | 86/103      |
| Lutron  | AYCL-153P   |
| Lutron  | AYCL-253P   |
| Lutron  | CTCL-153P   |
| Lutron  | CTRP-253P   |
| Leviton | DDMX1       |
| Leviton | DG6HD       |
| Leviton | DH6HD       |
| Leviton | DL6HD       |
| Leviton | DSEo6-10Z   |
| Leviton | DSL06       |
| Leviton | DSL06-1LZ   |
| Leviton | DSM10       |
| Eaton   | DUL06P-C2   |
| Lutron  | DVCL-153P   |
| Lutron  | DVCL-253P   |
| Lutron  | DVRP-253P   |
| Leviton | DW6HD       |
| Leviton | DZ6HD       |
| Lutron  | HQRA-PRO    |
| Lutron  | HQRD-10D    |
| Lutron  | HQRD-10NBD  |
| Lutron  | HQRD-6ND    |
| Lutron  | HQRD-HN6BRL |

|                |             |
|----------------|-------------|
| <b>Lutron</b>  | HQRD-PRO    |
| <b>Lutron</b>  | HRST-PRO-N  |
| <b>Leviton</b> | IPLo6       |
| <b>Lutron</b>  | LECL-153P   |
| <b>Lutron</b>  | MA-PRO      |
| <b>Lutron</b>  | MACL-153M   |
| <b>Lutron</b>  | MACL-LFQ    |
| <b>Lutron</b>  | MSCL-OP153M |
| <b>Lutron</b>  | NTCL-250    |
| <b>Lutron</b>  | NTRP-250    |
| <b>Lutron</b>  | PD-10NXD    |
| <b>Lutron</b>  | PD-6WCL     |
| <b>Lutron</b>  | RCL-153PNL  |
| <b>Eaton</b>   | RF9640-ND   |
| <b>Legrand</b> | RHCL450PTC  |
| <b>Leviton</b> | RNL06-10Z   |
| <b>Lutron</b>  | RRD-10D     |
| <b>Lutron</b>  | RRD-6CL     |
| <b>Lutron</b>  | RRD-6ND     |
| <b>Lutron</b>  | RRD-H6BRL   |
| <b>Lutron</b>  | RRD-PRO     |
| <b>Lutron</b>  | RRST-PRO-N  |
| <b>Satco</b>   | S11268      |
| <b>Lutron</b>  | SCL-153P    |
| <b>Lutron</b>  | ST-PRO-N    |
| <b>Lutron</b>  | STCL-153M   |
| <b>Eaton</b>   | SUF7        |
| <b>Lutron</b>  | TGCL-153PH  |

|         |           |
|---------|-----------|
| Leviton | TSL06     |
| Leviton | TSM10     |
| Lutron  | TTCL-100H |
| Eaton   | VSUL06D   |