



Project/Job Name:

Location:

Fixture Type:

Notes:

**S21924** - 14 Watt T8 LED; 4Ft; 6500K; Medium Bi Pin base; 50000 Average rated hours; 1800 Lumens; Type B; Ballast Bypass; Single or Double Ended Wiring



#### ELECTRICAL

Technology:	LED
Watts:	14W
Volts:	120V-277V
Lumens:	1800L
CRI:	80+
CCT (Kelvins):	6500K - Daylight
Beam Spread :	210
Hours Rated:	50000
Incandescent Equivalent :	75W
Fluorescent Equivalent :	25W/28W/30W/32W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C:	Type B
Lamp End Type :	Single Ended; Double Ended
THD:	20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

#### PACKAGING

Each UPC:	045923219245
Each Quantity:	1
Each Dimensions:	48.00 x 1.10 x 1.10

#### PHYSICAL

Base:	Medium Bi Pin
Shape:	T8
Finish:	Gloss White
Lens Finish:	Gloss White
Lens Material:	Glass
Dimensions (In.):	MOL: 47.78 - MOD: 1.1
Nominal Length:	48
Weight (Lbs.):	0.43
Material:	Glass
Housing Color:	White

#### COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cRUs - Recognized Component
Location Rating:	Damp
Indoor/Outoor:	Indoor; Outdoor
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PLCMB3ZLZZ39
BAA Compliant:	No
NOM Certificate No.:	NTE21CJTENo000079
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

#### INFO

Specification Note:	Built-in shock resistant circuit - (not hot until both ends are installed)
Installation Note:	Not for use in vapor tight fixtures.
Tube Guard Use:	Yes



**S21924** - 14 Watt T8 LED; 4Ft; 6500K; Medium Bi Pin base; 50000 Average rated hours; 1800 Lumens; Type B; Ballast Bypass; Single or Double Ended Wiring

## ACCESSORIES

---



**S8000** 5 Watt LED Emergency Driver; 120-277 Volts

---



**S8002** 10 Watt LED Emergency Driver; 120-277 Volt

---