



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S22211 - 5.5 Watt PAR20 LED; 90 CRI; 4000K; 40 deg. Beam Angle;
Medium base; 120 Volt



ELECTRICAL

Technology:	LED
Watts:	5.5W
Volts:	120V
Lumens:	500L
CRI:	90+
Rg Value :	67
CCT (Kelvins):	4000K - Cool White
Beam Spread :	40
Hours Rated:	15000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase
Incandescent Equivalent :	50W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Candlepower :	50
Power Factor :	0.7
Light Source:	LED
Voltage Type:	AC Only
Warranty:	2-Years

PACKAGING

Each UPC:	045923210440
Each Quantity:	1
Each Dimensions:	2.64 x 2.64 x 3.50

PHYSICAL

Base:	Medium
Shape:	PAR20
Finish:	Clear
Lens Finish:	Clear
Lens Material:	Plastic (PS)
Dimensions (In.):	MOL: 3.19 - MOD: 2.48
Weight (Lbs.):	0.09
Material:	Aluminum / Plastic
Housing Color:	White
Lensed:	Lensed Lamp

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor; Outdoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S22211 - 5.5 Watt PAR20 LED; 90 CRI; 4000K; 40 deg. Beam Angle;
Medium base; 120 Volt

DIMMER COMPATIBILITY

Leviton	6674
Satco	86/103
Lutron	AYCL-153P
Eaton	DAL06P-C2
Lutron	DVCL-153P
Leviton	DW6HD
Leviton	IPL06
Lutron	LECL-153PH
Lutron	MACL-153M
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	RCL-153PNL
Eaton	RF9640-ND
Legrand	RHCL450PTC
Lutron	RRD-6CL
Satco	S11268
Eaton	SAL06P