



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S22214 - 8.5 Watt PAR30L LED; 90 CRI; 3000K; 40 deg. Beam Angle; Medium base; 120 Volt



ELECTRICAL

Technology:	LED
Watts:	8.5W
Volts:	120V
Lumens:	700L
CRI:	90+
Rg Value :	53
CCT (Kelvins):	3000K - Soft White
Beam Spread :	40
Hours Rated:	15000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase or Adaptive Phase
Incandescent Equivalent :	75W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Candlepower :	75
Power Factor :	0.7
Light Source:	LED
Voltage Type:	AC Only
Warranty:	2-Years

PACKAGING

Each UPC:	045923210471
Each Quantity:	1
Each Dimensions:	3.90 x 3.90 x 4.80

PHYSICAL

Base:	Medium
Shape:	PAR30LN
Finish:	Clear
Lens Finish:	Clear
Lens Material:	Plastic (PS)
Dimensions (In.):	MOL: 4.41 - MOD: 3.74
Weight (Lbs.):	0.21
Material:	Aluminum / Plastic
Housing Color:	White
Lensed:	Lensed Lamp

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor; Outdoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S22214 - 8.5 Watt PAR30L LED; 90 CRI; 3000K; 40 deg. Beam Angle; Medium base; 120 Volt

DIMMER COMPATIBILITY

Leviton	66ELV
Satco	86/103
Legrand	ADTP703TU
Lutron	AYCL-153P
Lutron	CTRP-253P
Eaton	DAL06P-C2
Leviton	DDMX1
Eaton	DUL06P-C2
Lutron	DVCL-153P
Lutron	DVRP-253P
Leviton	DW6HD
Leviton	IPE04-1L
Lutron	LECL-153PH
Lutron	MA-PRO
Lutron	MACL-153M
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PD-10WX
Lutron	PD-6WCL
Lutron	RCL-153PNL
Eaton	RF9640-ND
Legrand	RH703PTUTC
Legrand	RHCL450PTC
Lutron	RRD-6CL
Lutron	RRD-PRO

Satco	S11268
Eaton	SALo6P
Eaton	SUF7
Eaton	TALo6P-C2
Eaton	VSULo6D