



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S22433 - 4 Watt PS52 LED vintage style Filament; Clear; 25000
Average rated hours; Medium Base; 120 Volt



ELECTRICAL

Technology:	LED
Watts:	4W
Volts:	120V
Lumens:	200L
CRI:	90+
CCT (Kelvins):	2150K -
Beam Spread :	320
Hours Rated:	25000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable or Triac
Incandescent Equivalent :	40W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Operating Position:	Base Up or Down
Power Factor :	0.91
Light Source:	LED Filament
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923224331
Each Quantity:	1
Each Dimensions:	7.17 x 7.17 x 12.80

INFO

ROI Category:	Screw
---------------	-------

PHYSICAL

Base:	Medium
Shape:	PS52
Finish:	Clear
Lens Finish:	Clear
Dimensions (In.):	MOL: 11.81 - MOD: 6.31
Weight (Lbs.):	0.3
Material:	Glass
Housing Color:	None

COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor; Outdoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	LOG2159ENC000762!LOG2159EN C000762-1
NOM Expiration Date:	7/30/2022
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S22433 - 4 Watt PS52 LED vintage style Filament; Clear; 25000
Average rated hours; Medium Base; 120 Volt

DIMMER COMPATIBILITY

Leviton	6674
Satco	86/103
LeGrand	ADTP703TU
Lutron	AYCL-153P
Lutron	CTRP-253P
Leviton	DSL06-1LZ
Leviton	DSM10-1LZ
Lutron	DVCL-153P
Lutron	DVLV-600P
Lutron	DVRP-253P
Leviton	IPL06-10Z
Lutron	LECL-153PH
Lutron	MA-PRO
Lutron	MACL-153M
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PD-6WCL
Lutron	RRD-6CL
Eaton	SAL06P2
Lutron	SLV-600P
Eaton	TAL06P-C2