



#### ELECTRICAL

Technology:	LED
Watts:	100W/80W/63W
Volts:	120V-277V
Lumens:	14000L/11200L/8820L
CRI:	80+
Rg Value :	9
CCT (Kelvins):	30K/40K/50K - Warm to Cool White
Beam Spread :	300
Hours Rated:	50000
Dimmable:	Yes-Dimmable - Only dimmable through wattage selection switch on lamp
Dimming Type :	Step Dimming
Incandescent Equivalent :	400W
HID Equivalent :	400W/320W/250W
Operating Temperature :	-40C (-40F) to +60C (+140F)
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Base Up or Down
Surge Protection :	Built-in surge protection - 4KV
THD:	14.50%
Power Factor :	>0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

Project/Job Name:

Location:

Fixture Type:

Notes:

**S23144** - 100/80/63 Wattage Selectable; LED HID Replacement; CCT Selectable; Type B; Ballast Bypass; Extended Mogul base; 100-277 Volt; ColorQuick Technology; PowerQuick Technology

• Wattage Selectable

• CCT Selectable



#### PHYSICAL

Base:	Mogul Extended
Shape:	Corn cob
Finish:	White
Lens Material:	Plastic
Dimensions (In.):	MOL: 10.55 - MOD: 5.11
Weight (Lbs.):	3.12
Material:	Plastic (PS)
Housing Color:	Dark Gray

#### COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating:	Damp
Indoor/Outoor:	Indoor; Outdoor
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-3KHWIB
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
B.U.G Rating:	B3-U5-G4
Restrictions:	No Restrictions

#### PACKAGING

Each UPC:	045923231445
Each Quantity:	1
Each Dimensions:	12.20 x 5.51 x 5.51

#### INFO

Additional Info:	Safety cable provided with S23143, S23144, S23145 ONLY and is required upon installation of these high bay, base-up applications. (Please See Instructions)
Installation Note:	Not for use in vapor tight fixtures.
Min Compartment Size:	Length: 9.85 in. Width: 9.85 in. Height: 11.54 in.