



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S23148 - 27/22/18 Wattage Selectable; LED HID Replacement;
CCT Selectable; Type B; Ballast Bypass; Medium base; 100-277 Volt;
ColorQuick Technology; PowerQuick Technology

- Wattage Selectable
- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	27W/22W/18W
Volts:	120V-277V
Lumens:	3780L/3080L/2520L
CRI:	80+
Rg Value :	28
CCT (Kelvins):	30K/40K/50K - Warm to Cool White
Beam Spread :	300
Hours Rated:	50000
Dimmable:	Yes-Dimmable - Only dimmable through wattage selection switch on lamp
Dimming Type :	Step Dimming
Incandescent Equivalent :	100W
HID Equivalent :	125W/100W/75W
Operating Temperature :	-40C (-40F) to +60C (+140F)
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
Surge Protection :	Built-in surge protection - 4KV
Power Factor :	>0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PHYSICAL

Base:	Medium
Shape:	Corncob
Finish:	White
Lens Material:	Plastic
Dimensions (In.):	MOL: 6.8g - MOD: 2.32
Weight (Lbs.):	0.66
Material:	Plastic (PS)
Housing Color:	Dark Gray

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor; Outdoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Both
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
B.U.G Rating:	B1-U5-G2
Restrictions:	No Restrictions

PACKAGING

Each UPC:	045923231483
Each Quantity:	1
Each Dimensions:	8.86 x 2.83 x 2.83

INFO

Additional Info:	Safety cable provided with S23143, S23144, S23145 ONLY and is required upon installation of these high bay, base-up applications. (Please See Instructions)
Installation Note:	Not for use in vapor tight fixtures.



S23148 - 27/22/18 Wattage Selectable; LED HID Replacement;
CCT Selectable; Type B; Ballast Bypass; Medium base; 100-277 Volt;
ColorQuick Technology; PowerQuick Technology

ACCESSORIES



92-410

Mogul To Medium E39 - E26 Reducer; 660W; 600V
