



ELECTRICAL

Technology:	LED
Watts:	63W/54W/45W
Volts:	120V-277V
Lumens:	8820L/7560L/6300L
CRI:	80+
Rg Value :	10
CCT (Kelvins):	30K/40K/50K - Warm to Cool White
Beam Spread :	300
Hours Rated:	50000
Incandescent Equivalent :	150W-250W
HID Equivalent :	250W/200W/175W
Operating Temperature :	-40C (-40F) to +60C (+140F)
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
Surge Protection:	Built-in surge protection - 4KV
THD:	14.10%
Power Factor :	>0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923231506
Each Quantity:	1
Each Dimensions:	11.57 x 3.66 x 3.66

INFO

Additional Info:	Safety cable provided with S23143, S23144, S23145 ONLY and is required upon installation of these high bay, base-up applications. (Please See Instructions)	
Installation Note:	Not for use in vapor tight fixtures.	
Min Compartment Size:	Length: 7.88 in. Width: 7.88 in.	

Project/Job Name:

Location:

Fixture Type:

Notes:

S23150 - 63/54/45 Wattage Selectable; LED HID Replacement; CCT Selectable; Type B; Ballast Bypass; Extended Mogul base; 100-277 Volt; ColorQuick Technology; PowerQuick Technology

- Wattage Selectable

- CCT Selectable



PHYSICAL

Base:	Mogul Extended
Shape:	Corncob
Finish:	White
Lens Material:	Plastic
Dimensions (In.):	MOL: 10.28 - MOD: 3.35
Weight (Lbs.):	1.8
Material:	Plastic (PS)
Housing Color:	Dark Gray

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating:	Damp
Indoor/Outoor:	Indoor; Outdoor
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-ZHMICR
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
B.U.G Rating:	B2-U5-G3
Restrictions:	No Restrictions