



ELECTRICAL

Technology:	LED
Watts:	27W
Volts:	277V-347V
Lumens:	3510L/3780L/3645L
CRI:	80+
Rg Value :	18
CCT (Kelvins):	30K/40K/50K - Warm to Cool White
Beam Spread :	300
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Incandescent Equivalent :	100W
HID Equivalent :	125W
Operating Temperature :	-30C (-22F) to +45C (+113F)
Lamp Ballast Type A/B/C:	Type B
Operating Position:	Universal
Surge Protection :	Built-in surge protection - 4KV
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923231612
Each Quantity:	1
Each Dimensions:	8.85 x 2.83 x 2.83

INFO

Installation Note:	Not for use in vapor tight fixtures.
--------------------	--------------------------------------

Project/Job Name:

Location:

Fixture Type:

Notes:

S23161 - 27 Watt LED HID Replacement; CCT Selectable; Type B; Ballast Bypass; Medium Base; 277-347 Volt; ColorQuick Technology

- CCT Selectable



PHYSICAL

Base:	Medium
Shape:	Corncob
Finish:	White
Lens Finish:	Clear
Lens Material:	Plastic
Dimensions (In.):	MOL: 6.76 - MOD: 2.36
Weight (Lbs.):	0.66
Material:	Aluminum / Polycarbonate (PC)
Housing Color:	Dark Gray
Sensor:	No

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating:	Damp
Indoor/Outoor:	Indoor; Outdoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP64
NSF Approved:	No
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S23161 - 27 Watt LED HID Replacement; CCT Selectable; Type B; Ballast Bypass; Medium Base; 277-347 Volt; ColorQuick Technology

ACCESSORIES



92-410

Mogul To Medium E39 - E26 Reducer; 660W; 600V
