



#### ELECTRICAL

Technology:	LED
Watts:	36W
Volts:	277V-480V
Lumens:	4680L/5040L/4860L
CRI:	80+
Rg Value :	11
CCT (Kelvins):	30K/40K/50K - Warm to Cool White
Beam Spread :	300
Hours Rated:	50000
Dimmable:	Yes-Dimmable - Only Dimmable Via Sensor Port
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Smart-Starfish App only
Incandescent Equivalent :	125W
HID Equivalent :	175W
Operating Temperature :	-30C (-22F) to +45C (+113F)
Lamp Ballast Type A/B/C:	Type B
Operating Position:	Universal
Surge Protection :	Built-in surge protection - 4KV
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

#### PACKAGING

Each UPC:	045923231629
Each Quantity:	1
Each Dimensions:	9.80 x 3.66 x 3.66

#### INFO

Installation Note:	Not for use in vapor tight fixtures.
--------------------	--------------------------------------

Project/Job Name:

Location:

Fixture Type:

Notes:

**S23162** - 36 Watt LED HID Replacement; CCT Selectable; Type B; Ballast Bypass; Medium Base; 277-480 Volt; ColorQuick Technology

- CCT Selectable



#### PHYSICAL

Base:	Medium
Shape:	Corncob
Finish:	White
Lens Finish:	Clear
Lens Material:	Plastic
Dimensions (In.):	MOL: 7.73 - MOD: 3.35
Weight (Lbs.):	1.4
Material:	Aluminum / Polycarbonate (PC)
Housing Color:	Dark Gray
Sensor:	Optional

#### COMPLIANCE

Safety Listing:	cUL - Certified; cUL - Classified; cRUs - Recognized Component
Location Rating:	Damp
Indoor/Outoor:	Indoor; Outdoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP64
NSF Approved:	No
RoHS Compliant:	Yes
Restrictions:	No Restrictions

**ACCESSORIES**

**80-954** Wifi Control for use with Hi-Pro 360 Lamps



**80-955** PIR Motion Sensor for use with Hi-Pro 360 Lamps



**80-956** Daylight Sensor for use with Hi-Pro 360 Lamps



**80-957** Motion Sensor for use with Hi-Pro 360 Lamps; Microwave Sensor



**92-410** Mogul To Medium E39 - E26 Reducer; 660W; 600V