



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S23413 - 4 Watt C15 LED Filament; Satin Spun; Clear; Medium base; 2700K; 300 Lumens; 120 Volt



ELECTRICAL

Technology:	LED
Watts:	4W
Volts:	120V
Lumens:	300L
CRI:	80+
CCT (Kelvins):	2700K - Warm White
Beam Spread :	300
Hours Rated:	15000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable
Incandescent Equivalent :	40W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Operating Position:	Universal
Power Factor :	0.9
Light Source:	LED Filament
Voltage Type:	AC Only
Warranty:	2-Years

PACKAGING

Each UPC:	045923234132
Each Quantity:	1
Each Dimensions:	2.40 x 2.40 x 5.08

INFO

ROI Category:	Screw
---------------	-------

PHYSICAL

Base:	Medium
Shape:	C15
Finish:	Satin Spun
Lens Finish:	Spun
Dimensions (In.):	MOL: 4.38 - MOD: 1.88
Weight (Lbs.):	0.81
Material:	Glass
Housing Color:	None

COMPLIANCE

Safety Listing:	cULus
Location Rating:	Damp
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	LOG215gENC000762!LOG215gENC000762-1
NOM Expiration Date:	7/30/2022
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	Not For Sale In: CA



S23413 - 4 Watt C15 LED Filament; Satin Spun; Clear; Medium base; 2700K; 300 Lumens; 120 Volt

DIMMER COMPATIBILITY

Leviton	6674
Satco	86/103
LeGrand	ADTP703TU
Lutron	AYCL-153P
Lutron	CTRP-253P
Leviton	DSL06-1LZ
Leviton	DSM10
Lutron	DVCL-153P
Lutron	DVRP-253P
Leviton	IPL06
Lutron	LECL-153PH
Lutron	MA-PRO
Lutron	MACL-153M
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PD-6WCL
Lutron	RRD-6CL
Eaton	SAL06P
Eaton	TAL06P-C2