



Project/Job Name:

Location:

Fixture Type:

Notes:

S28575 - 3.5 Watt; B11 LED; 3000K; Medium base; 120 Volt



ELECTRICAL

Technology:	LED
Watts:	3.5W
Volts:	120V
Lumens:	300L
CRI:	90+
Rg Value :	69
CCT (Kelvins):	3000K - Soft White
Beam Spread :	275
Hours Rated:	25000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable
Incandescent Equivalent :	40W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Operating Position:	Universal
Power Factor :	0.92
Light Source:	LED
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923285752
Each Quantity:	1
Each Dimensions:	1.50 x 1.50 x 4.33

INFO

ROI Category:	Screw
---------------	-------

PHYSICAL

Base:	Medium
Shape:	B11
Finish:	Clear
Lens Finish:	Clear
Dimensions (In.):	MOL: 3.78 - MOD: 1.38
Weight (Lbs.):	0.07
Material:	Plastic
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	NOM-030- ENER-2016!NTEC22EN003836
NOM Expiration Date:	5/29/2024
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S28575 - 3.5 Watt; B11 LED; 3000K; Medium base; 120 Volt

DIMMER COMPATIBILITY

Leviton	6672
Lutron	AYCL-153P
Lutron	CTRP-253P
Eaton	DALo6P-C2
Lutron	DVCL-153P
Lutron	DVRP-253P
Lutron	MA-PRO
Lutron	MACL-153M
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Satco	S11270