



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S28578 - 7.5 Watt; BR30 LED; 3000K; Medium base; 120 Volt



ELECTRICAL

Technology:	LED
Watts:	7.5W
Volts:	120V
Lumens:	650L
CRI:	90+
Rg Value :	62
CCT (Kelvins):	3000K - Warm White
Beam Spread :	105
Hours Rated:	25000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable
Incandescent Equivalent :	65W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Candlepower :	220
Power Factor :	0.92
Light Source:	LED
CBCP :	220
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923285783
Each Quantity:	1
Each Dimensions:	3.86 x 3.86 x 5.51

INFO

ROI Category:	Screw
---------------	-------

PHYSICAL

Base:	Medium
Shape:	BR30
Finish:	Frost
Lens Finish:	Frost
Dimensions (In.):	MOL: 5.157 - MOD: 3.74
Weight (Lbs.):	0.16
Material:	Plastic
Housing Color:	Gray
Lensed:	Lensed Lamp

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	LOG2059ENC006172
NOM Expiration Date:	7/21/2022
Enclosure Rating:	Open Rated Lamp
Rated For Enclosed Fixture:	No
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S28578 - 7.5 Watt; BR30 LED; 3000K; Medium base; 120 Volt

DIMMER COMPATIBILITY

Leviton	6672
LeGrand	ADTP703TU
Lutron	AYCL-153P
Lutron	CTRP-253P
Lutron	DVCL-153P
Lutron	LECL-153PH
Lutron	MACL-153M
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PD-6WCL
Satco	S11268
Satco	S11270
Eaton	SALo6P