



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S28652 - 16.5 Watt; A19 LED; 90CRI; 2700K; Medium base; 220 deg. Beam Angle; 120 Volt; 1600 Lumens; CEC



ELECTRICAL

Technology:	LED
Watts:	16.5W
Volts:	120V
Lumens:	1600L
CRI:	90+
Rg Value :	54
CCT (Kelvins):	2700K - Warm White
Beam Spread :	220
Hours Rated:	25000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable
Incandescent Equivalent :	100W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Power Factor :	0.95
Light Source:	LED
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923286520
Each Quantity:	1
Each Dimensions:	2.44 x 2.44 x 5.12

PHYSICAL

Base:	Medium
Shape:	A19
Finish:	Frost
Dimensions (In.):	MOL: 4.65 - MOD: 2.36
Weight (Lbs.):	0.16
Material:	Plastic
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	NTEC21ENM001063!NTEC21ENM001063-FR1
NOM Expiration Date:	1/17/2023
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S28652 - 16.5 Watt; A19 LED; 90CRI; 2700K; Medium base; 220 deg.
Beam Angle; 120 Volt; 1600 Lumens; CEC

DIMMER COMPATIBILITY

Legrand	ADTP703TU
Lutron	AYCL-153P
Lutron	CTRP-253P
Eaton	DALo6P-C2
Leviton	DDL06
Eaton	DULO6P-C2
Lutron	DVCL-153P
Lutron	DVRP-253P
Leviton	DW6HD
Lutron	LECL-153PH
Lutron	MA-PRO
Lutron	MACL-153M
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PD-10WX
Lutron	PD-6WCL
Eaton	RF9640-ND
Legrand	RH703PTUTC
Legrand	RHCL450PTC
Lutron	RRD-6CL
Satco	S11268
Satco	S11270
Eaton	SUF7
Eaton	VSULO6D