



#### ELECTRICAL

Technology:	LED
Watts:	13W
Volts:	120V-277V
Lumens:	1600L
CRI:	80+
CCT (Kelvins):	3500K - Neutral White
Beam Spread :	240
Hours Rated:	50000
Incandescent Equivalent :	50W
Fluorescent Equivalent :	28W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C:	Type B
Lamp End Type :	Single Ended; Double Ended
THD:	20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

#### PACKAGING

Each UPC:	045923286902
Each Quantity:	1
Each Dimensions:	46.00 x 0.85 x 0.85

#### INFO

Installation Note:	Not for use in vapor tight fixtures.
Shatterproof Type:	PET Coated

Project/Job Name:

Location:

Fixture Type:

Notes:

**S28690** - 13 Watt T5 LED; Miniature bi-pin base; 3500K; 50000 Average rated hours; 1600 Lumens; 120-277 Volt; Type B; Ballast Bypass; Single or Double Ended Wiring



#### PHYSICAL

Base:	Miniature Bi Pin
Shape:	T5
Finish:	Frost
Lens Finish:	Frost
Lens Material:	Glass
Dimensions (In.):	MOL: 46 - MOD: 0.83
Nominal Length:	48
Weight (Lbs.):	0.52
Material:	Glass
Housing Color:	White

#### COMPLIANCE

Safety Listing:	cULus - Classified; cULus - Certified; ETLus - Sanitation Recognized Component
Location Rating:	Damp
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PLYHW51UWNHJ
BAA Compliant:	No
NOM Certificate No.:	NTEEL21007402-SOL
NOM Expiration Date:	12/29/2021
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP20
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



**S28690** - 13 Watt T5 LED; Miniature bi-pin base; 3500K; 50000 Average rated hours; 1600 Lumens; 120-277 Volt; Type B; Ballast Bypass; Single or Double Ended Wiring

## ACCESSORIES

---



**S8000** 5 Watt LED Emergency Driver; 120-277 Volts

---



**S8002** 10 Watt LED Emergency Driver; 120-277 Volt

---