



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S28728 - 6 Watt LED PL 2-PIN; 4000K; 600 Lumens; GX23 base; 50000 Average rated hours; 360 deg. Beam Angle; 120-277 Volt; Type B; Ballast Bypass



ELECTRICAL

Technology:	LED
Watts:	6W
Volts:	120V-277V
Lumens:	600L
CRI:	80+
CCT (Kelvins):	4000K - Cool White
Beam Spread :	360
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Fluorescent Equivalent :	13W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923287282
Each Quantity:	1
Each Dimensions:	1.77 x 6.10 x 8.98

PHYSICAL

Base:	GX23
Shape:	PL
Finish:	Frost
Dimensions (In.):	MOL: 7.09 - MOD: 1.28
Weight (Lbs.):	0.11
Material:	Plastic
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified
Location Rating:	Damp
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	NTEC21ENM000316
NOM Expiration Date:	1/24/2023
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP20
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S28728 - 6 Watt LED PL 2-PIN; 4000K; 600 Lumens; GX23 base; 50000 Average rated hours; 360 deg. Beam Angle; 120-277 Volt; Type B; Ballast Bypass

ACCESSORIES

	S8000	5 Watt LED Emergency Driver; 120-277 Volts
--	--------------	--

	S8002	10 Watt LED Emergency Driver; 120-277 Volt
--	--------------	--
