



#### ELECTRICAL

Technology:	LED
Watts:	20W/30W/40W
Volts:	120V-277V
Lumens:	3200L/4700L/6000L
CRI:	80+
Rg Value :	8
CCT (Kelvins):	30K/40K/50K - Warm to Cool White
Beam Spread :	180
Hours Rated:	50000
Incandescent Equivalent :	100W
HID Equivalent :	175W
Operating Temperature :	-30C (-22F) to +45C (+113F)
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Horizontal
Surge Protection :	Built-in surge protection - 4KV
Power Factor :	>0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

#### PACKAGING

Each UPC:	045923289309
Each Quantity:	1
Each Dimensions:	4.02 x 4.02 x 10.15

#### INFO

Installation Note:	Not for use in vapor tight fixtures.
Min Compartment Size:	Length: 8 in. Width: 8 in. Height: 11 in.

Project/Job Name:

Location:

Fixture Type:

Notes:

**S28930** - 20/30/40 Wattage Selectable; LED Hi-Pro Wall Pack; CCT Selectable 3K/4K/5K; Type B; Ballast Bypass; Extended Mogul base; 100-277 Volt; ColorQuick Technology; PowerQuick Technology

- Wattage Selectable
- CCT Selectable



#### PHYSICAL

Base:	Mogul Extended
Shape:	Corncob
Finish:	White
Lens Material:	Plastic
Dimensions (In.):	MOL: 8.43 - MOD: 3.62
Weight (Lbs.):	1.65
Material:	Aluminum / Plastic
Housing Color:	White

#### COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating:	Damp
Indoor/Outoor:	Indoor; Outdoor
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PRDYRJJ3
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP64
NSF Approved:	No
RoHS Compliant:	Yes
B.U.G Rating:	B2-U3-G2
Restrictions:	No Restrictions



**S28930** - 20/30/40 Wattage Selectable; LED Hi-Pro Wall Pack; CCT Selectable 3K/4K/5K; Type B; Ballast Bypass; Extended Mogul base; 100-277 Volt; ColorQuick Technology; PowerQuick Technology

## ACCESSORIES

---



**80-929**

LED HID Surge Protector; 100-277V AC; 10KV Protection Level

---