



ELECTRICAL

Technology:	LED
Watts:	60W/70W/80W
Volts:	120V-277V
Lumens:	9000L/10150L/11200L
CRI:	80+
CCT (Kelvins):	30K/40K/50K - Soft White to Natural Light
Beam Spread :	180
Hours Rated:	50000
Dimmable:	Yes-Dimmable - Only dimmable through wattage selection switch on lamp
Dimming Type :	Step Dimming
Incandescent Equivalent :	400W
HID Equivalent :	200W/250W/320W
Operating Temperature :	-30C (-22F) to +45C (+113F)
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
Surge Protection :	Built-in surge protection - 4KV
THD:	<20%
Power Factor :	>0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923298837
Each Quantity:	1
Each Dimensions:	10.31 x 5.71 x 6.46

INFO

Installation Note:	Not for use in vapor tight fixtures.
Min Compartment Size:	Length: 11 in. Width: 11 in. Height: 9.2 in.

Project/Job Name:

Location:

Fixture Type:

Notes:

S28932R1 - LED Shoe Box Lamp; 60/70/80 Wattage Selectable; 3K/4K/5K CCT Selectable; 120-277 Volt; White Finish

• Wattage Selectable

• CCT Selectable



PHYSICAL

Base:	Mogul Extended
Shape:	Corncob
Finish:	White
Lens Material:	Polycarbonate (PC)
Dimensions (In.):	MOL: 8.86 - MOD: 8.9
Weight (Lbs.):	2.43
Material:	Aluminum
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating:	Damp
Indoor/Outoor:	Outdoor
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-ARHCWO
BAA Compliant:	No
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S28932R1 - LED Shoe Box Lamp; 60/70/80 Wattage Selectable;
3K/4K/5K CCT Selectable; 120-277 Volt; White Finish

ACCESSORIES



80-929

LED HID Surge Protector; 100-277V AC; 10KV Protection Level
