



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S29436 - 12.5 Watt; PAR30LN LED; 3000K; 60 deg. Beam Angle;
Medium base; 120 Volt



ELECTRICAL

Technology:	LED
Watts:	12.5W
Volts:	120V
Lumens:	1000L
CRI:	90+
CCT (Kelvins):	3000K - Soft White
Beam Spread :	60
Hours Rated:	25000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable
Incandescent Equivalent :	75W
Fluorescent Equivalent :	15W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Power Factor :	0.9
Light Source:	LED
CBCP :	843
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923294365
Each Quantity:	1
Each Dimensions:	3.94 x 3.94 x 4.92

PHYSICAL

Base:	Medium
Shape:	PAR30LN
Finish:	Clear
Lens Finish:	Clear
Lens Material:	Thermo Plastic (PBT)
Dimensions (In.):	MOL: 4.57 - MOD: 3.74
Weight (Lbs.):	0.35
Material:	Plastic
Housing Color:	Silver
Lensed:	Lensed Lamp

COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor; Outdoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	NOM-030- ENER-2016!NTEC22EN003805
NOM Expiration Date:	5/29/2024
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S29436 - 12.5 Watt; PAR30LN LED; 3000K; 60 deg. Beam Angle;
Medium base; 120 Volt

DIMMER COMPATIBILITY

Leviton	6631
Leviton	6674
Leviton	66ELV
Satco	86/103
Legrand	ADTP703TU
Lutron	AYCL-153P
Lutron	CTRP-253P
Eaton	DAL06P-C2
Leviton	DDL06-L
Leviton	DSL06-1LZ
Lutron	DVCL-153P
Lutron	DVRP-253P
Leviton	DW6HD
Leviton	IPE04
Leviton	IPL06
Lutron	LECL-153PH
Lutron	MA-PRO
Lutron	MACL-153M
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PD-6WCL
Legrand	RH703PTUTC
Legrand	RHCL450PTC
Lutron	RRD-6CL

Satco S11268

SATCO.COM | 800-437-2826

© Satco Products, Inc.
All rights reserved 2026

Satco	S11270
Lutron	SCL-153P
Eaton	SUF7
Eaton	TAL06P-C2