



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S29451 - 15 Watt; PAR38 LED; 3000K; 60 deg. Beam Angle;
Medium base; 120 Volt



ELECTRICAL

Technology:	LED
Watts:	15W
Volts:	120V
Lumens:	1200L
CRI:	90+
Rg Value :	4
CCT (Kelvins):	3000K - Soft White
Beam Spread :	60
Hours Rated:	25000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable
Incandescent Equivalent :	90W
Fluorescent Equivalent :	23W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Power Factor :	0.9
Light Source:	LED
CBCP :	876
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923294518
Each Quantity:	1
Each Dimensions:	4.92 x 4.92 x 5.51

PHYSICAL

Base:	Medium
Shape:	PAR38
Finish:	Clear
Lens Finish:	Clear
Lens Material:	Thermo Plastic (PBT)
Dimensions (In.):	MOL: 5 - MOD: 4.72
Weight (Lbs.):	0.49
Material:	Plastic
Housing Color:	Silver
Lensed:	Lensed Lamp

COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor; Outdoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	NTEC21EN001430
NOM Expiration Date:	3/29/2023
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S29451 - 15 Watt; PAR38 LED; 3000K; 60 deg. Beam Angle;
Medium base; 120 Volt

DIMMER COMPATIBILITY

Leviton	6631
Leviton	66ELV
Satco	86/103
Legrand	ADTP703TU
Lutron	AYCL-153P
Lutron	CTRP-253P
Eaton	DAL06P-C2
Lutron	DVCL-153P
Lutron	DVRP-253P
Leviton	DW6HD
Leviton	IPE04-1L
Lutron	LECL-153PH
Lutron	MA-PRO
Lutron	MACL-153M
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PD-6WCL
Legrand	RH703PTUTC
Legrand	RHCL450PTC
Lutron	RRD-6CL
Lutron	RRD-6ND
Satco	S11268
Satco	S11270
Lutron	SCL-153P
Eaton	SUF7

