



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S29810 - 11 Watt; A19 LED; 2700K; Medium base; 220 deg. Beam Angle; 120 Volt



ELECTRICAL

Technology:	LED
Watts:	11W
Volts:	120V
Lumens:	1100L
CRI:	80+
Rg Value :	4
CCT (Kelvins):	2700K - Warm White
Beam Spread :	220
Hours Rated:	25000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable
Incandescent Equivalent :	75W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Power Factor :	0.79
Light Source:	LED
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923298103
Each Quantity:	1
Each Dimensions:	2.44 x 2.44 x 4.80

PHYSICAL

Base:	Medium
Shape:	A19
Finish:	Frost
Dimensions (In.):	MOL: 4.331 - MOD: 2.362
Weight (Lbs.):	0.08
Material:	Plastic
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	NTEC20EN000584-1
NOM Expiration Date:	12/22/2022
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	Not For Sale In: CA



S29810 - 11 Watt; A19 LED; 2700K; Medium base; 220 deg. Beam Angle; 120 Volt

DIMMER COMPATIBILITY

Satco	86/103
Lutron	AYCL-153P
Lutron	CTRP-253P
Eaton	DAL06P-C2
Lutron	DVCL-153P
Lutron	DVRP-253P
Lutron	LECL-153PH
Lutron	MA-PRO
Lutron	MACL-153M
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PD-6WCL
Lutron	RRD-6CL
Satco	S11270