



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S29817 - 15 Watt; A19 LED; Frosted; 4000K; Medium base; 220 deg. Beam Angle; 120 Volt



ELECTRICAL

Technology:	LED
Watts:	15W
Volts:	120V
Lumens:	1600L
CRI:	80+
Rg Value :	17
CCT (Kelvins):	4000K - Cool White
Beam Spread :	220
Hours Rated:	25000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable
Incandescent Equivalent :	100W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Power Factor :	0.94
Light Source:	LED
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923298172
Each Quantity:	1
Each Dimensions:	2.44 x 2.44 x 5.12

PHYSICAL

Base:	Medium
Shape:	A19
Finish:	Frost
Dimensions (In.):	MOL: 4.646 - MOD: 2.362
Weight (Lbs.):	0.11
Material:	Plastic
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	NOM-030- ENER-2016!NTEC22EN003813
NOM Expiration Date:	5/29/2024
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	Not For Sale In: CA



S29817 - 15 Watt; A19 LED; Frosted; 4000K; Medium base; 220 deg.
Beam Angle; 120 Volt

DIMMER COMPATIBILITY

Lutron	AYCL-153P
Lutron	CTRP-253P
Lutron	DVCL-153P
Lutron	DVRP-253P
Lutron	LECL-153PH
Lutron	MA-PRO
Lutron	NTRP-250
Lutron	PD-6WCL
Lutron	RRD-PRO
Satco	S11270