




Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____



S29851 - 9 Watt LED PL 4-Pin; 3500K; 1050 Lumens; G24q base; 50000 Average rated hours; 120 Deg. Beam Angle; Type A; Ballast dependent



ELECTRICAL

Technology:	LED
Watts:	9W
Volts:	Ballast Dependent
Lumens:	1050L
CRI:	80+
CCT (Kelvins):	3500K - Neutral White
Beam Spread :	120
Hours Rated:	50000
Dimmable:	Yes-Dimmable - Only Dimmable with Compatible Dimming Ballasts
Fluorescent Equivalent :	26W/32W/42W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast required, check compatibility
Lamp Ballast Type A/B/C :	Type A
Operating Position:	Horizontal
THD:	20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	Ballast Dependent
Working Voltage :	Ballast dependent
Warranty:	5-Years

PHYSICAL

Base:	G24q (4-Pin)
Shape:	PL
Finish:	Frost
Dimensions (In.):	MOL: 6.63 - MOD: 1.09
Weight (Lbs.):	0.18
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus
Location Rating:	Damp
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PZGSP7ZP
BAA Compliant:	No
NOM Certificate No.:	NTEC21ENM000991
NOM Expiration Date:	1/21/2023
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

PACKAGING

Each UPC:	045923298516
Each Quantity:	1
Each Dimensions:	1.50 x 1.50 x 6.80