



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S29858** - 9 Watt LED PL 4-Pin; 3000K; 1050 Lumens; G24q base; 50000 Average rated hours; 120 Deg. Beam Angle; Type A; Ballast dependent



### ELECTRICAL

|                           |                                                               |
|---------------------------|---------------------------------------------------------------|
| Technology:               | LED                                                           |
| Watts:                    | 9W                                                            |
| Volts:                    | Ballast Dependent                                             |
| Lumens:                   | 1050L                                                         |
| CRI:                      | 80+                                                           |
| CCT (Kelvins):            | 3000K - Warm White                                            |
| Beam Spread :             | 120                                                           |
| Hours Rated:              | 50000                                                         |
| Dimmable:                 | Yes-Dimmable - Only Dimmable with Compatible Dimming Ballasts |
| Fluorescent Equivalent :  | 18W/26W/32W/42W                                               |
| Operating Temperature :   | -20C (-4F) to +45C (+113F)                                    |
| Ballasting Requirements : | Ballast required, check compatibility                         |
| Lamp Ballast Type A/B/C : | Type A                                                        |
| Operating Position:       | Base Up or Down                                               |
| THD:                      | 20%                                                           |
| Power Factor :            | 0.9                                                           |
| Light Source:             | LED                                                           |
| Voltage Type:             | Ballast Dependent                                             |
| Working Voltage :         | Ballast dependent                                             |
| Warranty:                 | 5-Years                                                       |

### PACKAGING

|                  |                    |
|------------------|--------------------|
| Each UPC:        | 045923298585       |
| Each Quantity:   | 1                  |
| Each Dimensions: | 2.00 x 2.00 x 4.80 |

### PHYSICAL

|                   |                       |
|-------------------|-----------------------|
| Base:             | G24q (4-Pin)          |
| Shape:            | PL                    |
| Finish:           | Frost                 |
| Dimensions (In.): | MOL: 4.69 - MOD: 1.91 |
| Weight (Lbs.):    | 0.23                  |
| Material:         | Aluminum / Plastic    |
| Housing Color:    | White                 |

### COMPLIANCE

|                             |                                     |
|-----------------------------|-------------------------------------|
| Safety Listing:             | cULus                               |
| Location Rating:            | Damp                                |
| DLC Approved:               | Yes                                 |
| DLC Classification:         | Standard                            |
| DLC ID:                     | PLT2KGHCCAYT                        |
| BAA Compliant:              | No                                  |
| NOM Certificate No.:        | NTEC21ENM001000!NTEC21ENM001000-FR1 |
| NOM Expiration Date:        | 1/18/2023                           |
| Enclosure Rating:           | Enclosed Rated Lamp                 |
| Rated For Enclosed Fixture: | Yes                                 |
| FCC Compliant:              | Yes                                 |
| RoHS Compliant:             | Yes                                 |
| Restrictions:               | No Restrictions                     |