



Project/Job Name:

Location:

Fixture Type:

Notes:

S29877 - 4.5 Watt B11 LED Filament; Clear; Candelabra base;
2700K; 350 Lumens; 120 Volt



ELECTRICAL

Technology:	LED
Watts:	4.5W
Volts:	120V
Lumens:	350L
CRI:	90+
Rg Value :	61
CCT (Kelvins):	2700K - Warm White
Beam Spread :	300
Hours Rated:	15000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Forward Phase or Reverse Phase or Triac
Incandescent Equivalent :	40W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Operating Position:	Universal
Power Factor :	0.9
Light Source:	LED Filament
Voltage Type:	AC Only
Warranty:	2-Years

PACKAGING

Each UPC:	045923298776
Each Quantity:	1
Each Dimensions:	1.38 x 1.38 x 3.94

PHYSICAL

Base:	Candelabra
Shape:	B11
Finish:	Clear
Lens Finish:	Clear
Dimensions (In.):	MOL: 3.75 - MOD: 1.25
Weight (Lbs.):	0.03
Material:	Glass
Housing Color:	None

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	LOG2059ENC002680
NOM Expiration Date:	5/27/2022
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S29877 - 4.5 Watt B11 LED Filament; Clear; Candelabra base;
2700K; 350 Lumens; 120 Volt

DIMMER COMPATIBILITY

Leviton	6674
Lutron	AYCL-153P
Lutron	CTRP-253P
Lutron	DVCL-153P
Lutron	DVRP-253P
Leviton	IPLo6
Lutron	LECL-153PH
Lutron	MACL-153M
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Lutron	SLV-600P