



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S29911-TF - 25 Watt T5 LED; Miniature bi-pin base; 5000K; 50000 Average rated hours; 3500 Lumens; Type A; Ballast dependent; Shatter Proof



ELECTRICAL

Technology:	LED
Watts:	25W
Volts:	Ballast Dependent
Lumens:	3500L
CRI:	80+
CCT (Kelvins):	5000K - Natural Light
Beam Spread :	185
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Incandescent Equivalent :	100W
Fluorescent Equivalent :	54W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast required, check compatibility
Lamp Ballast Type A/B/C :	Type A
Power Factor :	0.9
Light Source:	LED
Voltage Type:	Ballast Dependent
Warranty:	5-Years

PACKAGING

Each UPC:	
Each Quantity:	1
Each Dimensions:	47.60 x 0.59 x 0.59

INFO

Installation Note:	Not for use in vapor tight fixtures.
Integrated Features:	Integrated thermal fuse at pins
Shatterproof Type:	Yes
Includes:	Integrated thermal fuse at pins
ROI Category:	Linear Replacement Lamps (UL Type A)

PHYSICAL

Base:	Miniature Bi Pin
Shape:	T5
Finish:	Gloss
Lens Finish:	Gloss
Dimensions (In.):	MOL: 48 - MOD: 0.63
Nominal Length:	48
Weight (Lbs.):	0.3
Housing Color:	None

COMPLIANCE

Safety Listing:	cULus
Location Rating:	Damp
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	NTE21CJTEN000079
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions