



Project/Job Name:

Location:

Fixture Type:

Notes:

**S29924** - 40 Watt; 8 Foot; T8 LED; 4000K; Recessed Double Contact base; 50000 Average rated hours; 5500 Lumens; Type B; Ballast Bypass; Double Ended Wiring



#### ELECTRICAL

Technology:	LED
Watts:	40W
Volts:	120V-277V
Lumens:	5500L
CRI:	80+
CCT (Kelvins):	4000K - Cool White
Beam Spread :	210
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Incandescent Equivalent :	125W
Fluorescent Equivalent :	110W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Double Ended
THD:	25%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

#### PACKAGING

Each UPC:	045923299247
Each Quantity:	1
Each Dimensions:	1.00 x 1.00 x 96.13

#### PHYSICAL

Base:	Recessed Double Contact HO/VHO
Shape:	T8
Finish:	White
Lens Finish:	White
Dimensions (In.):	MOL: 93.88 - MOD: 1
Nominal Length:	96
Weight (Lbs.):	0.88
Material:	Glass
Housing Color:	White

#### COMPLIANCE

Safety Listing:	cULus - Classified; cULus - Certified; cRUus - Recognized Component
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

#### INFO

Additional Info:	Suitable for Emergency Lighting only with Satco EM Driver #S8002
Installation Note:	Not for use in vapor tight fixtures.
Min Compartment Size:	Length: 96.063 in. Width: 10.630 in. Height: 2.756 in.
Shatterproof Type:	PET Coated



**S29924** - 40 Watt; 8 Foot; T8 LED; 4000K; Recessed Double Contact base; 50000 Average rated hours; 5500 Lumens; Type B; Ballast Bypass; Double Ended Wiring

## ACCESSORIES

---



**S8002**

10 Watt LED Emergency Driver; 120-277 Volt

---