



ELECTRICAL

Technology:	LED
Watts:	80W/100W/130W
Volts:	120V-277V
Lumens:	11200L/14000L/18200L
CRI:	80+
Rg Value :	13
CCT (Kelvins):	4000K - Cool White
Beam Spread :	120
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Incandescent Equivalent :	400W
HID Equivalent :	250W/320W/400W
Operating Temperature :	-25C (-13F) to +50C (+122F)
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
Surge Protection:	Built-in surge protection - 4kV
Power Factor :	0.99
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923331145
Each Quantity:	1
Each Dimensions:	5.91 x 5.91 x 11.73

INFO

Installation Note:	Not for use in vapor tight fixtures.
Min Compartment Size:	Length: 15.75 in. Width: 14.96 in.

Project/Job Name:

Location:

Fixture Type:

Notes:

S33114 - 80/100/130 Wattage Selectable; LED; Hi-Bay; Type B; Ballast Bypass; Mogul Extended; 4000K; 100V-277V; 250W-400W Metal Halide Replacement

- Wattage Selectable



PHYSICAL

Base:	Mogul Extended
Shape:	Corncob
Finish:	White
Dimensions (In.):	MOL: 9.72 - MOD: 5.51
Weight (Lbs.):	2.7
Material:	Aluminum / Plastic
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating:	Damp
Indoor/Outoor:	Indoor; Outdoor
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Both
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP64
RoHS Compliant:	Yes
Restrictions:	No Restrictions