



#### ELECTRICAL

|                           |                                 |
|---------------------------|---------------------------------|
| Technology:               | LED                             |
| Watts:                    | 75W                             |
| Volts:                    | 120V-277V                       |
| Lumens:                   | 10500L                          |
| CRI:                      | 80+                             |
| Rg Value :                | 11                              |
| CCT (Kelvins):            | 5000K - Natural Light           |
| Beam Spread :             | 120/150/260                     |
| Hours Rated:              | 50000                           |
| Dimmable:                 | Non-Dimmable -                  |
| Incandescent Equivalent : | 750W                            |
| Fluorescent Equivalent :  | 105W                            |
| HID Equivalent :          | 400W                            |
| Operating Temperature :   | -20C (-4F) to +65C (+149F)      |
| Lamp Ballast Type A/B/C : | Type B                          |
| Operating Position:       | Base Up or Down                 |
| Surge Protection :        | Built-in surge protection - 4KV |
| THD:                      | <20%                            |
| Power Factor :            | >0.9                            |
| Light Source:             | LED                             |
| Voltage Type:             | AC Only; Range Voltage          |
| Warranty:                 | 5-Years                         |

#### PACKAGING

|                  |                     |
|------------------|---------------------|
| Each UPC:        | 045923397691        |
| Each Quantity:   | 1                   |
| Each Dimensions: | 4.96 x 10.16 x 4.96 |

#### INFO

|                       |   |
|-----------------------|---|
| Additional Info:      | PIR Sensor available as an accessory              |
| Specification Note:   | Closed 260 deg; Partial 150 deg; Open 120 deg     |
| Installation Note:    | Not for use in vapor tight fixtures.              |
| Min Compartment Size: | Width: 9.30 in. Depth: 9.30 in. Height: 10.50 in. |
| ROI Category:         | Replacement Lamps for High-Bay Luminaires         |

Project/Job Name:

Location:

Fixture Type:

Notes:

**S39769** - 75 Watt LED HID Replacement; 5000K; Mogul Extended base; Adjustable Beam Angle; Type B Ballast Bypass; 100-277 Volt

- Has Driver



#### PHYSICAL

|                   |   |
|-------------------|---|
| Base:             | Mogul Extended                          |
| Shape:            | Corncob                                 |
| Finish:           | Clear                                   |
| Lens Finish:      | Clear                                   |
| Lens Material:    | Thermo Plastic (PBT)                    |
| Dimensions (In.): | MOL: 8.46 - MOD: 4.08                   |
| Weight (Lbs.):    | 2.4                                     |
| Material:         | Aluminum / Steel / Thermo Plastic (PBT) |
| Housing Color:    | White                                   |
| Sensor:           | Optional Add-On                         |

#### COMPLIANCE

|                             |   |
|-----------------------------|---|
| Safety Listing:             | cULus - Certified; cULus - Classified; cULus - Listed |
| Location Rating:            | Damp  |
| Indoor/Outoor:              | Indoor; Outdoor                                       |
| DLC Approved:               | No  |
| BAA Compliant:              | No  |
| Enclosure Rating:           | Enclosed Rated Lamp                                   |
| Rated For Enclosed Fixture: | Yes   |
| FCC Compliant:              | Yes   |
| IP Rating:                  | IP64  |
| RoHS Compliant:             | Yes   |
| Restrictions:               | No Restrictions                                       |



**S39769** - 75 Watt LED HID Replacement; 5000K; Mogul Extended base; Adjustable Beam Angle; Type B Ballast Bypass; 100-277 Volt

## ACCESSORIES

---



**86-215**

LED PIR Sensor for use with Utility/Multi Beam Fixtures; White Finish

---