



Project/Job Name:

Location:

Fixture Type:

Notes:

S39906-TF - 17 Watt T8 LED; 4Ft; 4000K; Medium Bi Pin base; 50000 Average rated hours; 2200 Lumens; Type B; Ballast Bypass; Single or Double Ended Wiring; Shatterproof coated



ELECTRICAL

Technology:	LED
Watts:	17W
Volts:	120V-277V
Lumens:	2200L
CRI:	80+
CCT (Kelvins):	4000K - Cool White
Beam Spread :	210
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Incandescent Equivalent :	90W
Fluorescent Equivalent :	45W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Single Ended; Double Ended
THD:	20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	
Each Quantity:	1
Each Dimensions:	48.00 x 1.10 x 1.10

INFO

Installation Note:	Not for use in vapor tight fixtures.
Shatterproof Type:	Shatterproof coated

PHYSICAL

Base:	Medium Bi Pin
Shape:	T8
Finish:	Gloss White
Lens Finish:	Gloss White
Lens Material:	Glass
Dimensions (In.):	MOL: 47.78 - MOD: 1.1
Nominal Length:	48
Weight (Lbs.):	0.44
Material:	Glass
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Classified
Location Rating:	Damp
Indoor/Outoor:	Indoor; Outdoor
DLC Approved:	No
BAA Compliant:	No
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions