



Project/Job Name:

Location:

Fixture Type:

Notes:

S39913 - 14 Watt T8 LED; 4Ft; 3000K; Medium Bi Pin base; 50000 Average rated hours; 1700 Lumens; Type B; Ballast Bypass; Single or Double Ended Wiring



ELECTRICAL

Technology:	LED
Watts:	14W
Volts:	120V-277V
Lumens:	1700L
CRI:	80+
CCT (Kelvins):	3000K - Warm White
Beam Spread :	210
Hours Rated:	50000
Incandescent Equivalent :	75W
Fluorescent Equivalent :	25W/28W/30W/32W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Lamp End Type :	Single Ended; Double Ended
THD:	20%
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923399138
Each Quantity:	1
Each Dimensions:	48.00 x 1.10 x 1.10

PHYSICAL

Base:	Medium Bi Pin
Shape:	T8
Finish:	Gloss White
Lens Finish:	Gloss White
Lens Material:	Glass
Dimensions (In.):	MOL: 47.78 - MOD: 1.1
Nominal Length:	48
Weight (Lbs.):	0.43
Material:	Glass
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cRUus - Recognized Component
Location Rating:	Damp
Indoor/Outdoor:	Indoor; Outdoor
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	PLSTQCAUKZMU
BAA Compliant:	No
NOM Certificate No.:	NTE21CJTEN000079
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
NSF Approved:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

INFO

Additional Info:	Equivalent CCT selectable option available in S11766
Specification Note:	Built-in shock resistant circuit - (not hot until both ends are installed)
Installation Note:	Not for use in vapor tight fixtures.
Tube Guard Use:	Yes



S39913 - 14 Watt T8 LED; 4Ft; 3000K; Medium Bi Pin base; 50000 Average rated hours; 1700 Lumens; Type B; Ballast Bypass; Single or Double Ended Wiring

ACCESSORIES

	S8000	5 Watt LED Emergency Driver; 120-277 Volts
--	--------------	--

	S8002	10 Watt LED Emergency Driver; 120-277 Volt
--	--------------	--
