



Project/Job Name:

Location:

Fixture Type:

Notes:

**S39927** - 12 Watt T8 LED; 3Ft; 3500K; Medium Bi Pin base; 50000 Average rated hours; 1400 Lumens; Type B; Ballast Bypass; Single or Double Ended Wiring



## ELECTRICAL

|                           |                            |
|---------------------------|----------------------------|
| Technology:               | LED                        |
| Watts:                    | 12W                        |
| Volts:                    | 120V-277V                  |
| Lumens:                   | 1400L                      |
| CRI:                      | 80+                        |
| CCT (Kelvins):            | 3500K - Neutral White      |
| Beam Spread :             | 210                        |
| Hours Rated:              | 50000                      |
| Incandescent Equivalent : | 50W                        |
| Fluorescent Equivalent :  | 25W                        |
| Operating Temperature :   | -20C (-4F) to +45C (+113F) |
| Ballasting Requirements : | Ballast Bypass             |
| Lamp Ballast Type A/B/C : | Type B                     |
| Lamp End Type :           | Single Ended; Double Ended |
| THD:                      | 20%                        |
| Power Factor :            | 0.9                        |
| Light Source:             | LED                        |
| Voltage Type:             | AC Only; Range Voltage     |
| Warranty:                 | 5-Years                    |

## PACKAGING

|                  |                     |
|------------------|---------------------|
| Each UPC:        | 045923399275        |
| Each Quantity:   | 1                   |
| Each Dimensions: | 36.00 x 1.10 x 1.10 |

## INFO

|                     |                                                                            |
|---------------------|----------------------------------------------------------------------------|
| Additional Info:    | Equivalent CCT selectable option available in S11765                       |
| Specification Note: | Built-in shock resistant circuit - (not hot until both ends are installed) |
| Installation Note:  | Not for use in vapor tight fixtures.                                       |
| Tube Guard Use:     | Yes                                                                        |

## PHYSICAL

|                   |                       |
|-------------------|-----------------------|
| Base:             | Medium Bi Pin         |
| Shape:            | T8                    |
| Finish:           | Gloss White           |
| Lens Finish:      | Gloss White           |
| Lens Material:    | Glass                 |
| Dimensions (In.): | MOL: 35.78 - MOD: 1.1 |
| Nominal Length:   | 36                    |
| Weight (Lbs.):    | 0.34                  |
| Material:         | Glass                 |
| Housing Color:    | White                 |

## COMPLIANCE

|                             |                                                                     |
|-----------------------------|---------------------------------------------------------------------|
| Safety Listing:             | cULus - Certified; cULus - Classified; cRUus - Recognized Component |
| Location Rating:            | Damp                                                                |
| Indoor/Outdoor:             | Indoor; Outdoor                                                     |
| DLC Approved:               | Yes                                                                 |
| DLC Classification:         | Standard                                                            |
| DLC ID:                     | PLGWY2SBB1MN                                                        |
| BAA Compliant:              | No                                                                  |
| NOM Certificate No.:        | NTE21CJTEN000079                                                    |
| Rated For Enclosed Fixture: | Yes                                                                 |
| FCC Compliant:              | Yes                                                                 |
| NSF Approved:               | Yes                                                                 |
| RoHS Compliant:             | Yes                                                                 |
| Restrictions:               | No Restrictions                                                     |



**S39927** - 12 Watt T8 LED; 3Ft; 3500K; Medium Bi Pin base; 50000 Average rated hours; 1400 Lumens; Type B; Ballast Bypass; Single or Double Ended Wiring

ACCESSORIES

---

|                                                                                  |              |                                            |
|----------------------------------------------------------------------------------|--------------|--------------------------------------------|
|  | <b>S8000</b> | 5 Watt LED Emergency Driver; 120-277 Volts |
|----------------------------------------------------------------------------------|--------------|--------------------------------------------|

---

|                                                                                  |              |                                            |
|----------------------------------------------------------------------------------|--------------|--------------------------------------------|
|  | <b>S8002</b> | 10 Watt LED Emergency Driver; 120-277 Volt |
|----------------------------------------------------------------------------------|--------------|--------------------------------------------|

---