



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S49394 - 54 Watt LED HID Replacement; 5000K; Extended Mogul base; Type B Ballast Bypass; Economy Hi-Pro



ELECTRICAL

Technology:	LED
Watts:	54W
Volts:	120V-277V
Lumens:	7452L
CRI:	80+
Rg Value :	12
CCT (Kelvins):	5000K - Natural Light
Beam Spread :	300
Hours Rated:	35000
Dimmable:	Non-Dimmable -
Incandescent Equivalent :	300W
HID Equivalent :	250W
Operating Temperature :	-25C (-13F) to +55C (+131F)
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
Surge Protection :	Built-in surge protection - 3KV
Power Factor :	>0.9
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	3-Years

PACKAGING

Each UPC:	045923493942
Each Quantity:	1
Each Dimensions:	3.94 x 3.94 x 9.84

PHYSICAL

Base:	Mogul Extended
Shape:	Corncob
Finish:	White
Lens Finish:	Clear
Lens Material:	Polycarbonate (PC)
Dimensions (In.):	MOL: 8.78 - MOD: 3.35
Weight (Lbs.):	1.9
Material:	Aluminum / Polycarbonate (PC)
Housing Color:	White
Sensor:	No

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor; Outdoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	NOM-030-ENER-2016!NTEC22EN004472
NOM Expiration Date:	6/16/2022
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
IP Rating:	IP65
RoHS Compliant:	Yes
Restrictions:	No Restrictions

INFO

Additional Info:	Safety cable provided with S49395, S49396, S49397, S49675, S49676, S49677 ONLY and is required upon installation of these high bay, base-up applications. (Please See Instructions)
Installation Note:	Not for use in vapor tight fixtures.
Min Compartment Size:	Length: 8 in. Width: 8 in. Height: 15.75 in.