



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S49395** - 80 Watt LED HID Replacement; 5000K; Extended Mogul base; Type B Ballast Bypass; Economy Hi-Pro



### ELECTRICAL

|                           |                                 |
|---------------------------|---------------------------------|
| Technology:               | LED                             |
| Watts:                    | 80W                             |
| Volts:                    | 120V-277V                       |
| Lumens:                   | 11040L                          |
| CRI:                      | 80+                             |
| Rg Value :                | 11                              |
| CCT (Kelvins):            | 5000K - Natural Light           |
| Beam Spread :             | 300                             |
| Hours Rated:              | 35000                           |
| Dimmable:                 | Non-Dimmable -                  |
| Incandescent Equivalent : | 400W                            |
| HID Equivalent :          | 320W                            |
| Operating Temperature :   | -25C (-13F) to +55C (+131F)     |
| Lamp Ballast Type A/B/C : | Type B                          |
| Operating Position:       | Base Up or Down                 |
| Surge Protection :        | Built-in surge protection - 4KV |
| Power Factor :            | >0.9                            |
| Light Source:             | LED                             |
| Voltage Type:             | AC Only; Range Voltage          |
| Warranty:                 | 3-Years                         |

### PACKAGING

|                  |                     |
|------------------|---------------------|
| Each UPC:        | 045923493959        |
| Each Quantity:   | 1                   |
| Each Dimensions: | 5.31 x 5.31 x 10.24 |

### PHYSICAL

|                   |                               |
|-------------------|-------------------------------|
| Base:             | Mogul Extended                |
| Shape:            | Corncob                       |
| Finish:           | White                         |
| Lens Finish:      | Clear                         |
| Lens Material:    | Polycarbonate (PC)            |
| Dimensions (In.): | MOL: 8.69 - MOD: 4.72         |
| Weight (Lbs.):    | 3                             |
| Material:         | Aluminum / Polycarbonate (PC) |
| Housing Color:    | White                         |
| Sensor:           | No                            |

### COMPLIANCE

|                             |                                                       |
|-----------------------------|-------------------------------------------------------|
| Safety Listing:             | cULus - Certified; cULus - Classified; cULus - Listed |
| Location Rating:            | Damp                                                  |
| Indoor/Outdoor:             | Indoor; Outdoor                                       |
| DLC Approved:               | No                                                    |
| BAA Compliant:              | No                                                    |
| NOM Certificate No.:        | NOM-030-ENER-2016!NTEC22EN004472                      |
| NOM Expiration Date:        | 6/16/2022                                             |
| Enclosure Rating:           | Enclosed Rated Lamp                                   |
| Rated For Enclosed Fixture: | Yes                                                   |
| FCC Compliant:              | Yes                                                   |
| IP Rating:                  | IP65                                                  |
| RoHS Compliant:             | Yes                                                   |
| Restrictions:               | No Restrictions                                       |

### INFO

|                       |                                                                                                                                                                                     |
|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Additional Info:      | Safety cable provided with S49395, S49396, S49397, S49675, S49676, S49677 ONLY and is required upon installation of these high bay, base-up applications. (Please See Instructions) |
| Installation Note:    | Not for use in vapor tight fixtures.                                                                                                                                                |
| Min Compartment Size: | Length: 9.25 in. Width: 9.25 in. Height: 17.32 in.                                                                                                                                  |
| Includes:             | Safety Cable                                                                                                                                                                        |