



ELECTRICAL

| | |
|---------------------------|---------------------------------|
| Technology: | LED |
| Watts: | 54W |
| Volts: | 120V-277V |
| Lumens: | 7398L |
| CRI: | 80+ |
| Rg Value : | 11 |
| CCT (Kelvins): | 4000K - Cool White |
| Beam Spread : | 300 |
| Hours Rated: | 35000 |
| Dimmable: | Non-Dimmable - |
| Incandescent Equivalent : | 300W |
| HID Equivalent : | 250W |
| Operating Temperature : | -25C (-13F) to +55C (+131F) |
| Lamp Ballast Type A/B/C : | Type B |
| Operating Position: | Universal |
| Surge Protection : | Built-in surge protection - 3kV |
| Power Factor : | >0.9 |
| Light Source: | LED |
| Voltage Type: | AC Only; Range Voltage |
| Warranty: | 3-Years |

PACKAGING

| | |
|------------------|--------------------|
| Each UPC: | 045923496745 |
| Each Quantity: | 1 |
| Each Dimensions: | 3.94 x 3.94 x 9.84 |

Project/Job Name:

Location:

Fixture Type:

Notes:

S49674 - 54 Watt LED HID Replacement; 4000K; Extended Mogul base; Type B Ballast Bypass; Economy Hi-Pro



PHYSICAL

| | |
|-------------------|-------------------------------|
| Base: | Mogul Extended |
| Shape: | Corncob |
| Finish: | White |
| Lens Finish: | Clear |
| Lens Material: | Polycarbonate (PC) |
| Dimensions (In.): | MOL: 8.78 - MOD: 3.35 |
| Weight (Lbs.): | 1.9 |
| Material: | Aluminum / Polycarbonate (PC) |
| Housing Color: | White |
| Sensor: | No |

COMPLIANCE

| | |
|-----------------------------|---|
| Safety Listing: | cULus - Certified; cULus - Classified; cULus - Listed |
| Location Rating: | Damp |
| Indoor/Outoor: | Indoor; Outdoor |
| DLC Approved: | No |
| BAA Compliant: | No |
| NOM Certificate No.: | NOM-030-ENER-2016!NTEC22EN004472 |
| NOM Expiration Date: | 6/16/2022 |
| Enclosure Rating: | Enclosed Rated Lamp |
| Rated For Enclosed Fixture: | Yes |
| FCC Compliant: | Yes |
| IP Rating: | IP65 |
| RoHS Compliant: | Yes |
| Restrictions: | No Restrictions |

INFO

| | |
|-----------------------|---|
| Additional Info: | Safety cable provided with S49395, S49396, S49397, S49675, S49676, S49677 ONLY and is required upon installation of these high bay, base-up applications. (Please See Instructions) |
| Installation Note: | Not for use in vapor tight fixtures. |
| Min Compartment Size: | Length: 8 in. Width: 8 in. Height: 15.75 in. |