



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S49992** - 10 Watt; 3 Foot LED T8; Medium Bi Pin base; 4000K; 50000 Average rated hours; 1450 Lumens; Type A; Ballast dependent



### ELECTRICAL

|                           |                                                                                |
|---------------------------|--------------------------------------------------------------------------------|
| Technology:               | LED                                                                            |
| Watts:                    | 10W                                                                            |
| Volts:                    | Ballast Dependent                                                              |
| Lumens:                   | 1450L                                                                          |
| CRI:                      | 80+                                                                            |
| CCT (Kelvins):            | 4000K - Cool White                                                             |
| Beam Spread :             | 210                                                                            |
| Hours Rated:              | 50000                                                                          |
| Dimmable:                 | Yes-Dimmable - Only in Type A mode; Check Ballast MFG for Dimmer Compatibility |
| Dimmable Down To %:       | 100 to 20 percent                                                              |
| Incandescent Equivalent : | 125W                                                                           |
| Fluorescent Equivalent :  | 25W/21W                                                                        |
| Operating Temperature :   | -20C (-4F) to +45C (+113F)                                                     |
| Ballasting Requirements : | Ballast required, check compatibility                                          |
| Lamp Ballast Type A/B/C : | Type A                                                                         |
| THD:                      | 20%                                                                            |
| Power Factor :            | 0.9                                                                            |
| Light Source:             | LED                                                                            |
| Voltage Type:             | Ballast Dependent                                                              |
| Warranty:                 | 5-Years                                                                        |

### PACKAGING

|                  |                     |
|------------------|---------------------|
| Each UPC:        | 045923499920        |
| Each Quantity:   | 1                   |
| Each Dimensions: | 36.00 x 1.10 x 1.10 |

### INFO

|                    |                                                                                         |
|--------------------|-----------------------------------------------------------------------------------------|
| Installation Note: | Not for use in vapor tight fixtures.                                                    |
| Tube Guard Use:    | Approved for use with tube guards when operated on Low or Normal ballast factor systems |

### PHYSICAL

|                   |                       |
|-------------------|-----------------------|
| Base:             | Medium Bi Pin         |
| Shape:            | T8                    |
| Finish:           | Gloss White           |
| Lens Finish:      | Gloss White           |
| Lens Material:    | Glass                 |
| Dimensions (In.): | MOL: 35.78 - MOD: 1.1 |
| Nominal Length:   | 36                    |
| Weight (Lbs.):    | 0.31                  |
| Material:         | Glass                 |
| Housing Color:    | White                 |

### COMPLIANCE

|                             |                                   |
|-----------------------------|-----------------------------------|
| Safety Listing:             | cULus - Certified; cULus - Listed |
| Location Rating:            | Damp                              |
| Indoor/Outdoor:             | Indoor                            |
| DLC Approved:               | Yes                               |
| DLC Classification:         | Standard                          |
| DLC ID:                     | PLLNVHPCLEEZ                      |
| BAA Compliant:              | No                                |
| NOM Certificate No.:        | NTE21CJTEN000079                  |
| Rated For Enclosed Fixture: | Yes                               |
| FCC Compliant:              | Yes                               |
| NSF Approved:               | Yes                               |
| RoHS Compliant:             | Yes                               |
| Restrictions:               | No Restrictions                   |