



Project/Job Name:

Location:

Fixture Type:

Notes:

S8605 - 6.5 Watt; LED MR16; 3000K; 40 deg. Beam Angle; GU5.3 base; 12 Volt AC/DC; Carded



ELECTRICAL

Technology:	LED
Watts:	6.5W
Volts:	12V
Lumens:	500L
CRI:	80+
Rg Value :	10
CCT (Kelvins):	3000K - Soft White
Beam Spread :	40
Hours Rated:	25000
Dimmable:	Yes-Dimmable - Check the transformer/driver MFG for dimmer compatibility
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable or Triac
Incandescent Equivalent :	50W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Candlepower :	1060
Power Factor :	0.93
Light Source:	LED
CBCP :	1060
Voltage Type:	AC/DC
Warranty:	5-Years

PHYSICAL

Base:	Bi Pin GU5.3
Shape:	MR16
Finish:	Gray
Lens Finish:	Silver Back
Dimensions (In.):	MOL: 1.772 - MOD: 1.969
Weight (Lbs.):	0.1
Material:	Plastic
Housing Color:	Gray
Lensed:	Lensed Lamp

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
Indoor/Outoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	ANC2101J00000796
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

PACKAGING

Each UPC:	045923086052
Each Quantity:	1
Each Dimensions:	2.09 x 4.88 x 8.38

INFO

ROI Category:	Screw
---------------	-------



S8605 - 6.5 Watt; LED MR16; 3000K; 40 deg. Beam Angle; GU5.3 base; 12 Volt AC/DC; Carded

DIMMER COMPATIBILITY

Lutron	CTRP-253P
Lutron	DVLV-600P
Lutron	MA-PRO
Lutron	NTRP-250
Lutron	SLV-600P