



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S8677 - 6.5 Watt; LED MR16; 3000K; 25 deg. Beam Angle; GU10 base; 120 Volt



ELECTRICAL

Technology:	LED
Watts:	6.5W
Volts:	120V
Lumens:	500L
CRI:	80+
CCT (Kelvins):	3000K - Warm White
Beam Spread :	25
Hours Rated:	25000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable or Triac
Incandescent Equivalent :	50W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Candlepower :	1100
Spot Type :	NFL - Narrow Flood
Power Factor :	0.92
Light Source:	LED
CBCP :	1100
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923086779
Each Quantity:	1
Each Dimensions:	2.00 x 2.00 x 2.75

INFO

ROI Category:	Screw
---------------	-------

PHYSICAL

Base:	Bi Pin GU10
Shape:	MR16
Finish:	White
Lens Finish:	Array
Dimensions (In.):	MOL: 2.28 - MOD: 1.97
Weight (Lbs.):	0.08
Material:	Plastic
Housing Color:	White
Lensed:	Lensed Lamp

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	LOG2159ENC000558!LOG2159ENC000558-1
NOM Expiration Date:	7/15/2022
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

DIMMER COMPATIBILITY

Leviton	6674
Satco	86/103
LeGrand	ADTP703TU
Lutron	CTRP-253P
Leviton	DSE06
Lutron	DVCL-153P
Lutron	DVLV-600P
Lutron	DVRP-253P
Lutron	HQRD-6NA
Lutron	HW-RPM-4A-120
Lutron	LECL-153PH
Lutron	MA-PRO
Lutron	MRF2-6ELV
Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PHPM-WBX-120
Legrand	RH703PTUTC
Lutron	RRD-PRO
Satco	S11268
Satco	S11270
Lutron	SLV-600P