



ELECTRICAL

Technology:	LED
Watts:	8W
Volts:	120V-277V
Lumens:	960L
CRI:	80+
CCT (Kelvins):	5000K - Natural Light
Beam Spread :	120
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Fluorescent Equivalent :	13W/18W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Ballasting Requirements :	Ballast Bypass
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Universal
Light Source:	LED
Voltage Type:	Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923087592
Each Quantity:	1
Each Dimensions:	7.28 x 1.65 x 1.65

INFO

ROI Category:	Screw
---------------	-------

Project/Job Name:

Location:

Fixture Type:

Notes:

S8759 - 8 Watt LED PL Medium base; 5000K; Type B; Ballast Bypass; 960 Lumens; 50000 Average rated hours; 120 deg. Beam Angle; 120-277 Volt



PHYSICAL

Base:	Medium
Shape:	PL
Finish:	Frost
Dimensions (In.):	MOL: 6.88 - MOD: 1.38
Weight (Lbs.):	0.24
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Damp
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	NTEC21ENM000991
NOM Expiration Date:	1/21/2023
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	Not For Sale In: CA



S8759 - 8 Watt LED PL Medium base; 5000K; Type B; Ballast Bypass; 960 Lumens; 50000 Average rated hours; 120 deg. Beam Angle; 120-277 Volt

ACCESSORIES



S8000 5 Watt LED Emergency Driver; 120-277 Volts



S8002 10 Watt LED Emergency Driver; 120-277 Volt
