



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S8926** - 40 Watt LED Hi-lumen directional lamp for commercial fixture applications; 3000K; Mogul base; 100-277 Volt; Ballast bypass - Type B



### ELECTRICAL

Technology:	LED
Watts:	40W
Volts:	120V-277V
Lumens:	5600L
CRI:	85+
CCT (Kelvins):	3000K - Warm White
Beam Spread :	180
Hours Rated:	50000
Dimmable:	Non-Dimmable -
Incandescent Equivalent :	125W
HID Equivalent :	250W
Operating Temperature :	-29C (-20.2F) to +60C (+140F)
Lamp Ballast Type A/B/C :	Type B
Operating Position:	Horizontal
Power Factor :	0.91
Light Source:	LED
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

### PACKAGING

Each UPC:	045923089268
Each Quantity:	1
Each Dimensions:	4.02 x 4.02 x 11.54

### INFO

Installation Note:	Not for use in vapor tight fixtures.
Min Compartment Size:	Length: 11 in. Width: 8 in. Depth: 8 in.
ROI Category:	Replacement Lamps for High-Bay Luminaires

### PHYSICAL

Base:	Mogul
Shape:	Corncob
Finish:	Clear
Lens Finish:	Clear
Dimensions (In.):	MOL: 10.63 - MOD: 3.56
Weight (Lbs.):	1
Material:	Aluminum
Housing Color:	White/Grey

### COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Classified
Location Rating:	Damp
DLC Approved:	No
BAA Compliant:	No
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions