



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

Sg201 - 6 Watt; G25 Globe LED; 3000K; Medium base; 120 Volt



ELECTRICAL

Technology:	LED
Watts:	6W
Volts:	120V
Lumens:	450L
CRI:	80+
Rg Value :	10
CCT (Kelvins):	3000K - Soft White
Beam Spread :	175
Hours Rated:	25000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable or Triac
Incandescent Equivalent :	40W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Operating Position:	Universal
Power Factor :	0.9
Light Source:	LED
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923092015
Each Quantity:	1
Each Dimensions:	3.23 x 3.23 x 4.65

PHYSICAL

Base:	Medium
Shape:	G25
Finish:	White
Lens Finish:	White
Dimensions (In.):	MOL: 4.25 - MOD: 3.15
Weight (Lbs.):	0.17
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	NTEC22EN002140
NOM Expiration Date:	3/24/2024
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	Not For Sale In: CA



Sg201 - 6 Watt; G25 Globe LED; 3000K; Medium base; 120 Volt

DIMMER COMPATIBILITY

Leviton	6674
Satco	86/103
LeGrand	ADTP703TU
Lutron	AYCL-153P
Lutron	CTRP-253P
Lutron	DVCL-153P
Lutron	DVLV-600P
Lutron	LECL-153PH
Lutron	MA-PRO
Lutron	MACL-153M
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PD-6WCL
Lutron	SLV-600P
Eaton	TALo6P-C2