



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S9385** - 6.5 Watt; LED MR16; 5000K; 40 deg. Beam Angle; GU10 base; 120 Volt



#### ELECTRICAL

|                           |                                                       |
|---------------------------|-------------------------------------------------------|
| Technology:               | LED                                                   |
| Watts:                    | 6.5W                                                  |
| Volts:                    | 120V                                                  |
| Lumens:                   | 500L                                                  |
| CRI:                      | 80+                                                   |
| Rg Value :                | 22                                                    |
| CCT (Kelvins):            | 5000K - Natural Light                                 |
| Beam Spread :             | 40                                                    |
| Hours Rated:              | 25000                                                 |
| Dimmable:                 | Yes-Dimmable -                                        |
| Dimmable Down To %:       | 100 to 20 percent                                     |
| Dimming Type :            | Forward Phase or Reverse Phase<br>or Phase Selectable |
| Incandescent Equivalent : | 50W                                                   |
| Operating Temperature :   | -25C (-13F) to +45C (+113F)                           |
| Candlepower :             | 700                                                   |
| Spot Type :               | FL - Flood                                            |
| Power Factor :            | 0.92                                                  |
| Light Source:             | LED                                                   |
| CBCP :                    | 700                                                   |
| Voltage Type:             | AC Only                                               |
| Warranty:                 | 5-Years                                               |

#### PACKAGING

|                  |                    |
|------------------|--------------------|
| Each UPC:        | 045923093852       |
| Each Quantity:   | 1                  |
| Each Dimensions: | 1.97 x 1.97 x 2.80 |

#### PHYSICAL

|                   |                         |
|-------------------|-------------------------|
| Base:             | Bi Pin GU10             |
| Shape:            | MR16                    |
| Finish:           | White                   |
| Lens Finish:      | Array White             |
| Dimensions (In.): | MOL: 2.165 - MOD: 1.969 |
| Weight (Lbs.):    | 0.08                    |
| Housing Color:    | White                   |
| Lensed:           | Lensed Lamp             |

#### COMPLIANCE

|                             |                                   |
|-----------------------------|-----------------------------------|
| Safety Listing:             | cULus - Certified; cULus - Listed |
| Location Rating:            | Damp                              |
| Indoor/Outdoor:             | Indoor                            |
| DLC Approved:               | No                                |
| BAA Compliant:              | No                                |
| NOM Certificate No.:        | NTEC21ENM000994                   |
| NOM Expiration Date:        | 1/19/2023                         |
| Enclosure Rating:           | Enclosed Rated Lamp               |
| Rated For Enclosed Fixture: | Yes                               |
| FCC Compliant:              | Yes                               |
| RoHS Compliant:             | Yes                               |
| Restrictions:               | No Restrictions                   |



**S9385** - 6.5 Watt; LED MR16; 5000K; 40 deg. Beam Angle; GU10 base; 120 Volt

#### DIMMER COMPATIBILITY

|         |               |
|---------|---------------|
| Leviton | 6674          |
| Satco   | 86/103        |
| LeGrand | ADTP703TU     |
| Lutron  | CTRP-253P     |
| Lutron  | DVCL-153P     |
| Lutron  | DVRP-253P     |
| Lutron  | HQRD-6NA      |
| Lutron  | HW-RPM-4A-120 |
| Lutron  | LECL-153PH    |
| Lutron  | MRF2-6ELV     |
| Lutron  | NTCL-250      |
| Lutron  | PHPM-WBX-120  |
| Legrand | RH703PTUTC    |
| Satco   | S11268        |
| Satco   | S11270        |