



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S9389 - 6.5 Watt PAR16 LED; 5000K; 40 deg. Beam Angle; Medium base; 120 Volt



ELECTRICAL

Technology:	LED
Watts:	6.5W
Volts:	120V
Lumens:	500L
CRI:	80+
Rg Value :	19
CCT (Kelvins):	5000K - Natural Light
Beam Spread :	40
Hours Rated:	25000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable or Triac
Incandescent Equivalent :	60W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Candlepower :	700
Power Factor :	0.92
Light Source:	LED
CBCP :	700
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923093890
Each Quantity:	1
Each Dimensions:	2.13 x 2.13 x 3.00

INFO

ROI Category:	Screw
---------------	-------

PHYSICAL

Base:	Medium
Shape:	PAR16
Finish:	Clear
Lens Finish:	Clear
Dimensions (In.):	MOL: 2.88 - MOD: 2
Weight (Lbs.):	0.11
Housing Color:	White
Lensed:	Lensed Lamp

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	NTEC21EN000188
NOM Expiration Date:	1/18/2023
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



Sg389 - 6.5 Watt PAR16 LED; 5000K; 40 deg. Beam Angle; Medium base; 120 Volt

DIMMER COMPATIBILITY

Leviton	6674
Satco	86/103
LeGrand	ADTP703TU
Lutron	AYCL-153P
Lutron	CTRP-253P
Leviton	DSM10-1LZ
Lutron	DVCL-153P
Lutron	DVLV-600P
Lutron	LECL-153PH
Lutron	MA-PRO
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PD-6WCL
Eaton	SALo6P2
Lutron	SLV-600P
Eaton	TALo6P-C2