



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S9550 - 1.6W; LED MR11 LED; 3000K; 40 deg. beam spread; G4 base; 12 Volt AC/DC



ELECTRICAL

Technology:	LED
Watts:	1.6W
Volts:	12V
Lumens:	200L
CRI:	80+
CCT (Kelvins):	3000K - Warm White
Beam Spread :	40
Hours Rated:	25000
Dimmable:	Yes-Dimmable - Check the transformer/driver MFG for dimmer compatibility
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable or Triac
Incandescent Equivalent :	10W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Light Source:	LED
Voltage Type:	AC/DC
Warranty:	5-Years

PACKAGING

Each UPC:	045923095504
Each Quantity:	1
Each Dimensions:	1.50 x 1.50 x 1.63

INFO

ROI Category:	Screw
---------------	-------

PHYSICAL

Base:	Bi Pin G4
Shape:	MR11
Finish:	Clear
Lens Finish:	Clear
Dimensions (In.):	MOL: 1.56 - MOD: 1.31
Weight (Lbs.):	0.02
Material:	Plastic
Housing Color:	Clear
Lensed:	Lensed Lamp

COMPLIANCE

Safety Listing:	cETLus
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	ANC2101J00000796
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S9550 - 1.6W; LED MR11 LED; 3000K; 40 deg. beam spread; G4 base; 12 Volt AC/DC

DIMMER COMPATIBILITY

Lutron	CTRP-253P
Lutron	DVLV-600P
Lutron	MA-PRO
Lutron	MALV-600
Lutron	NTRP-250
Lutron	SLV-600P