



#### ELECTRICAL

Technology:	LED
Watts:	3W
Volts:	12V
Lumens:	330L
CRI:	80+
CCT (Kelvins):	3000K - Warm White
Beam Spread :	40
Hours Rated:	25000
Dimmable:	Yes-Dimmable - Check the transformer/driver MFG for dimmer compatibility
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable or Triac
Incandescent Equivalent :	20W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Light Source:	LED
Voltage Type:	AC/DC
Warranty:	5-Years

#### PACKAGING

Each UPC:	045923095528
Each Quantity:	1
Each Dimensions:	2.00 x 2.00 x 2.00

#### INFO

ROI Category:	Screw
---------------	-------

Project/Job Name:

Location:

Fixture Type:

Notes:

**S9552** - 3 Watt; LED MR16 LED; 3000K; 40 deg. Beam Angle; GU5.3 base; 12 Volt



#### PHYSICAL

Base:	Bi Pin GU5.3
Shape:	MR16
Finish:	Clear
Lens Finish:	Clear
Dimensions (In.):	MOL: 2 - MOD: 2
Weight (Lbs.):	0.03
Housing Color:	Clear
Lensed:	Lensed Lamp

#### COMPLIANCE

Safety Listing:	cULus
Location Rating:	Damp
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	ANC2101J00000796
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



**S9552** - 3 Watt; LED MR16 LED; 3000K; 40 deg. Beam Angle; GU5.3 base; 12 Volt

#### DIMMER COMPATIBILITY

---

<b>Lutron</b>	CTRP-253P
<b>Lutron</b>	DVLV-600P
<b>Lutron</b>	MA-PRO
<b>Lutron</b>	MALV-600
<b>Lutron</b>	NTRP-250
<b>Lutron</b>	SLV-600P