



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S9630 - 6.5 Watt; LED R20; 2700K; 107 deg. Beam Angle; Medium base; 120 Volt; Dimmable



ELECTRICAL

Technology:	LED
Watts:	6.5W
Volts:	120V
Lumens:	525L
CRI:	80+
Rg Value :	11
CCT (Kelvins):	2700K - Warm White
Beam Spread :	107
Hours Rated:	25000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable
Incandescent Equivalent :	45W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Candlepower :	180
Power Factor :	0.92
Light Source:	LED
CBCP :	180
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923096303
Each Quantity:	1
Each Dimensions:	2.60 x 2.60 x 4.25

PHYSICAL

Base:	Medium
Shape:	R20
Finish:	Frost
Lens Finish:	Frost
Dimensions (In.):	MOL: 3.94 - MOD: 2.5
Weight (Lbs.):	0.09
Housing Color:	Gray
Lensed:	Lensed Lamp

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	LOG2059ENC006172
NOM Expiration Date:	7/21/2022
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	Not For Sale In: CA



Sg630 - 6.5 Watt; LED R20; 2700K; 107 deg. Beam Angle; Medium base; 120 Volt; Dimmable

DIMMER COMPATIBILITY

Lutron	AYCL-153P
Lutron	CTCL-153P
Lutron	CTRP-253P
Lutron	DVCL-153P
Lutron	DVRP-253P
Lutron	GT-5NEM
Lutron	GTJ-5NEM
Lutron	HQRD-10ND
Lutron	HQRD-6NA
Lutron	HQRD-HN6BRL
Lutron	HW-RPM-4A-120
Lutron	HW-RPM-4U-120
Lutron	MACL-153M
Lutron	MRF2-6ELV
Lutron	MRF2S-6ELV
Lutron	MSCL-OP153M
Lutron	NTRP-250
Lutron	PD-6WCL
Lutron	PHPM-WBX-120
Lutron	RRD-HN6BRL
Satco	S11268
Satco	S11270
Lutron	SCL-153P
Leviton	VPE04-1LZ