



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S9637 - 11.5 Watt; LED BR40; 5000K; 103 deg. Beam Angle;
Medium base; 120 Volt; dimmable



ELECTRICAL

Technology:	LED
Watts:	11.5W
Volts:	120V
Lumens:	940L
CRI:	80+
Rg Value :	17
CCT (Kelvins):	5000K - Natural Light
Beam Spread :	103
Hours Rated:	25000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable
Incandescent Equivalent :	65W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Candlepower :	340
Power Factor :	0.9
Light Source:	LED
CBCP :	340
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923096372
Each Quantity:	1
Each Dimensions:	5.12 x 5.12 x 6.81

PHYSICAL

Base:	Medium
Shape:	BR40
Finish:	Frost
Lens Finish:	Frost
Lens Material:	Polycarbonate (PC)
Dimensions (In.):	MOL: 6.457 - MOD: 5
Weight (Lbs.):	0.31
Material:	Plastic
Housing Color:	Gray
Lensed:	Lensed Lamp

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	LOG2059ENC002606
NOM Expiration Date:	5/25/2022
Enclosure Rating:	Open Rated Lamp
Rated For Enclosed Fixture:	No
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	Not For Sale In: CA



S9637 - 11.5 Watt; LED BR40; 5000K; 103 deg. Beam Angle;
Medium base; 120 Volt; dimmable

DIMMER COMPATIBILITY

Leviton	6674
Lutron	CTCL-153P
Lutron	CTRP-253P
Lutron	DVCL-153P
Lutron	DVRP-253P
Lutron	LQSE-4A1-D
Lutron	MACL-153M
Lutron	MQSE-4A1-D
Lutron	NTRP-250
Lutron	PHPM-WBX-120
Satco	S11268
Satco	S11270
Lutron	SCL-153P
Lutron	SZ-6ND