



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S9704 - 10 Watt; A19 LED; 3000K; Medium base; 220 deg. Beam Angle; 90CRI; 120 Volt



ELECTRICAL

Technology:	LED
Watts:	10W
Volts:	120V
Lumens:	800L
CRI:	90+
Rg Value :	68
CCT (Kelvins):	3000K - Soft White
Beam Spread :	220
Hours Rated:	25000
Dimmable:	Yes-Dimmable -
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable
Incandescent Equivalent :	60W
Operating Temperature :	-25C (-13F) to +45C (+113F)
Power Factor :	0.93
Light Source:	LED
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923097041
Each Quantity:	1
Each Dimensions:	2.44 x 2.44 x 4.80

INFO

Three Way:	No
------------	----

PHYSICAL

Base:	Medium
Shape:	A19
Finish:	Frost
Dimensions (In.):	MOL: 4.331 - MOD: 2.362
Weight (Lbs.):	0.06
Material:	Plastic
Housing Color:	White

COMPLIANCE

Safety Listing:	cULus - Certified; cULus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	No
BAA Compliant:	No
NOM Certificate No.:	LOG2059ENC005639
NOM Expiration Date:	9/17/2022
Enclosure Rating:	Enclosed Rated Lamp
Rated For Enclosed Fixture:	Yes
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions



S9704 - 10 Watt; A19 LED; 3000K; Medium base; 220 deg. Beam Angle; 90CRI; 120 Volt

DIMMER COMPATIBILITY

Leviton	6674
Satco	86/103
LeGrand	ADTP703TU
Lutron	AYCL-153P
Lutron	CTRP-253P
Leviton	DSE06
Lutron	DVCL-153P
Lutron	LECL-153PH
Lutron	MACL-153M
Lutron	NTCL-250
Lutron	NTRP-250
Lutron	PD-6WCL
Satco	S11268
Satco	S11270
Eaton	TAL06P-C2